



**Sales and Service**

Quotation : O-196049-Q-16306  
Quote doc: Q-16306-WOODBURY PARKS REC BLDG  
SOURCEWELL ID # 117077

December 7, 2020

**Quote for**

Mr. Joe Gianzero  
Town of Woodbury Parks Dept.

**Prepared by**

Ed Cheung  
Senior Sales Representative  
890 Zerega Avenue  
Bronx NY 10473  
United States  
Phone: (718) 892-2400  
www.cummins.com

Quote for: Town of Woodbury Parks Dept.

Quote valid until: February 5, 2021

Thank you for your inquiry. We are pleased to quote as follows.

ITEM NUMBER	DESCRIPTION	Quantity
1	<b>Cummins OTPC Transfer Switch: 225A</b> Application - Utility to Genset Listing - UL 1008 / CSA Certification Cabinet - Type 1 Poles - 3 (Solid Neutral) Frequency - 60 Hz System - Single Phase, 2 or 3 Wire Voltage - 240 Volts AC Level 1 Transfer Switch Control Display - Digital Transfer Switch Warranty - Year 0 - 2: Parts, Labor and Travel Year 3 - 5: Parts Only Year 6 - 10: Main Contacts Only	1
2	<b>12VDC Engine Starting Battery - 700CCA</b>	1
3	<b>Annunciator-Panel Mounted With Enclosure (RS485)</b>	1
4	<b>Service - start up &amp; building testing</b>	1



5	<b>Enclosure Kit-Onan Green, Sound Level 2</b>	1
6	<b>Freight FLAT BED DELIVERY</b>	1
7	<b>C50D6, Diesel Genset, 60Hz, 50kW</b>	1
	U.S. EPA, Stationary Emergency Application	
	C50D6, 50kW, 60Hz, Standby, Diesel Genset	
	Duty Rating - Standby Power (ESP)	
	Listing - UL 2200	
	NFPA 110 Type 10 Level 1 Capable	
	Emission Certification, EPA, Tier 3, NSPS CI Stationary Emergency	
	Cert - Seismic, IBC2000, IBC2003, IBC2006, IBC2009, IBC2012	
	Voltage - 120 / 240, 1 Phase, 3 Wire	
	Alternator - 60HZ, 4L, 240 / 120V, 1 Phase, 105C, 40C Ambient, Increased Motor Starting (IMS)	
	Exciter / Regulator - Permanent Magnet Generator, 3 Phase Sensor	
	Alternator Heater, 120 Volt AC	
	Aluminum Sound Attenuated Level 2 Enclosure, with Exhaust System	
	Enclosure Color - Green, Aluminum	
	Enclosure - Wind Load 180 MPH, ASCE7-10	
	Skidbase - Housing Ready	
	Fuel Tank - Regional, Dual Wall, Sub Base, 48 Hour Minimum	
	High Fuel Level Switch, 90%	
	Low Fuel Level Switch, 40%	
	Mechanical Fuel Gauge	
	5 Gallon Lockable Spill Containment Fuel Fill Box	
	Switch - Fuel Tank, Rupture Basin	
	Control Mounting - Right Facing	
	PowerCommand1.1 Controller	
	Gauge - Oil Pressure	
	Meters - AC Output Analog (kVA)	
	Stop Switch - Emergency	
	Relays - Aux, Qty2 - 25A - 15 Volts DC / 10A - 30 Volts DC	
	Control Display Language - English	



**Sales and  
Service**

Load Connection - Single  
Circuit Breaker, Location A, 225A, 2P, 600 Volts AC, 80%, UL  
Right CB - None  
Engine Governor - Electronic, Isochronous  
Engine Starter - 12 Volt DC Motor  
Engine Air Cleaner - Normal Duty  
Battery Charging Alternator  
Battery Charger - 6 Amp, Regulated  
Engine Cooling - Radiator, High Ambient Air Temperature, Ship Fitted  
Shutdown - Low Coolant Level  
Extension - Coolant Drain  
Engine Coolant - 50% Antifreeze, 50% Water Mixture  
Coolant Heater  
Extension - Oil Drain  
Engine Oil  
Test Record - Safety Shutdowns  
Genset Warranty - 2 Years Base  
Literature - English  
Packing - Skid, Poly Bag  
Larger Battery Rack  
Green Sound Level 2 Intake Baffle - Ship Loose

**Grand Total USD 30,930.00**

**SOURCEWELL PRICING OPTIONS:**

- A. 50 KW Diesel Generator Package - \$ 30,930.00
- B. 30 KW Diesel Generator Package - \$ 28,750.00

Please refer on Purchase Order our SOURCEWELL ID # 120617 – CMM along with your SOURCEWELL ID # 117077.

NOTE: Quote Grand Total does not include any tax.